

Sig Marine®

SIG-200 Diesel Stove

Model #20125 - 5" Flue
Model #20124 - 4" Flue



WEIGHT	100 LBS
HEIGHT	23.75"
WIDTH	22"
DEPTH	20"
FLUE SIZE	4" DIAMETER (also available in 5")
FUEL CONSUMPTION	1.14 gal/24 hr - Low 3 gal / 24hr - High
HEAT OUTPUT	6,000 BTU - 15,000 BTU
FUEL OPTIONS	Diesel, Kerosene, Stove Oil
HOT WATER OPTIONS	1 turn coil / 2 turn coil
INSTALL CONSIDERATIONS	Install facing bow or stern,

Options:

- valve calibration for diesel
(standard), stove oil or kerosene,

Product Includes:

Fire-viewing window,
drip pan, cleaning tool,
Cast Iron cooktop
Draft assist fan
(12v, 24v or 32v;)

The Sig 200 is Sig Marine's smaller diesel stove. It features an efficient 5.5" Stainless Steel burner. With large cast iron radiant tops, these stoves are great for producing heat, for cooking and for producing hot water with the optional water coil heat exchangers. This stove uses 4 inch diameter flue components, but is available in 5" as well. Use with Sig Marine stainless steel flue pipe, 45 degree elbows, barometric damper, deck-fitting and exhaust caps. The heat can be extended with the optional hot air heat exchanger stack robber system.

Installation guidelines require a minimum 4 foot flue rise and heat clearances of more than 6 inches or a min of 2 inches to an insulated surface. See the owner's manuals for details. A barometric damper is recommended on all installations. Fuel pumps, gravity feed tanks, and filters are available.

Standard fuel metering for this stove is the Sig Marine 3D valve for diesel. Stove Oil (2S) and Kerosene (2K) are also available as options or add ons. A 12V draft assist fan is included, but can be changed to 24V or 32V if needed.